



## GREEN STRAND

**6 x 19** Seale

*Fils ronds  
Round Strand  
Cordones redondos*

Diam. (mm)	AME TEXTILE FIBER CORE ALMA EN FIBRA			AME ACIER STEEL CORE ALMA METALICA			AME MIXTE MIXED CORE ALMA MIXTA		
	Kg/m	Charge de rupture minimum Min. Breaking load Carga de rotura mínima		Kg/m	Charge de rupture minimum Min. Breaking load Carga de rotura mínima		Kg/m	Charge de rupture minimum Min. Breaking load Carga de rotura mínima	
		(kN)	(Kg)		(kN)	(Kg)		(kN)	(Kg)
12	0,51	76,6	7.800	-	-	-	-	-	-
13	0,62	94,0	9.600	-	-	-	-	-	-
14	0,69	106	10.700	-	-	-	-	-	-
15	0,82	124	12.700	-	-	-	-	-	-
16	0,95	145	14.800	-	-	-	-	-	-
17	1,05	159	16.200	-	-	-	-	-	-
18	1,20	182	18.600	1,36	197	20.100	1,28	190,8	19.500
19	1,26	192	19.600	1,45	210	21.400	1,36	202,3	20.600
20	1,47	224	22.800	1,68	244	24.800	1,58	235,2	24.000
22	1,72	261	26.600	1,94	282	28.800	1,84	273,2	27.900
24	2,04	310	31.600	2,32	338	34.400	2,19	326,3	33.300
25	-	-	-	-	-	-	2,42	360,9	36.800
26	2,48	388	39.500	2,82	422	43.000	2,65	406,9	41.500
28	2,86	447	45.500	3,22	482	49.100	3,05	466,5	47.600
29	-	-	-	3,41	518	52.700	-	-	-
30	3,27	512	52.100	3,70	561	57.100	3,49	540,5	55.100
32	3,70	579	59.000	4,20	638	64.900	3,97	613,3	62.500