



## SUPER ATLANTIC

**6 x K 26** Seale Warrington

*Torons compactés  
Compacted strands  
Cordones compactados*



Diam. (mm)	AME TEXTILE - FIBER CORE – ALMA EN FIBRA			AME ACIER – STEEL CORE – ALMA METALICA		
	Kg/m	Charge de rupture minimum Min. Breaking load Carga de rotura mínima		Kg/m	Charge de rupture minimum Min. Breaking load Carga de rotura mínima	
		(kN)	(Kg)		(kN)	(Kg)
19	1,46	232	23.700	-	-	-
20	1,60	256	26.100	1,79	266	27.200
22	1,92	307	31.300	2,15	320	32.700
24	2,29	365	37.200	2,57	390	39.700
25	2,52	402	41.000	2,81	426	43.500
26	2,68	428	43.700	3,00	461	47.100
28	3,17	506	51.600	3,55	552	56.200
30	3,61	576	58.700	4,03	632	64.500
32	4,11	655	66.800	4,60	722	73.600
34	4,64	739	75.300	5,20	817	83.300
36	5,20	829	84.600	5,80	913	93.100
38	-	-	-	6,45	1.015	103.500
40	-	-	-	7,21	1.133	115.500
42	-	-	-	7,91	1.244	126.800
44	-	-	-	8,70	1.367	139.400